

Technical Data Sheet

AF-817

Ingredient Silicone oil and hydrophobic particles of water emulsion

Warranty 6 months (kept in a cool, dry place at room temperature)

Applications AF-817 is used in

- Added to textile printing and dyeing process
- Add printing and dyeing auxiliaries

Features ● Good compatibility with the system

- Easy to disperse in water
- Suitable for a wide pH range and temperature range

Physical indicators

Exterior White or yellowish milky liquid

Solid content (29-31) %

pH value 6.0-9.0

Viscosity, 25°C 2000-10000mPa.s

Instructions ● It can be used directly or diluted to a low content.

-
- Can be diluted directly with water, but need to be used immediately, if the dilution needs to be stored for a certain time, you can consult our company, our company will provide professional dilution method.
 - The addition amount is generally 10~1000ppm, and the optimal addition amount is determined according to the actual situation on site.

Precautions

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
- Storage at room temperature (5-40°C), away from direct sunlight
- Refer to the product's Material Safety Data Sheet (MSDS) before use

Usage

- Not for human injection

restrictions

- This product is not tested or represented as suitable for medical or pharmaceutical use

Package

- 25kg/50kg/200kg plastic drum or 1000kg IBC drum
-

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.