

Technical Data Sheet

AF-715

Ingredient	Fatty acid esters
Warranty	12 months (kept in a cool, dry place at room temperature)
Applications	<p>AF-715 is used in paper coating, papermaking white water, sewage treatment.</p> <ul style="list-style-type: none">● Eliminate air bubbles from paper paint● Degassing and defoaming of papermaking white water● Sewage treatment process, such as coal washing plant wastewater treatment
Features	<ul style="list-style-type: none">● The product has outstanding anti-foaming effect● For water treatment systems with viscous foam or containing a large amount of particulate matter, this product has obvious advantages in defoaming and foam suppression properties● The product disperses easily in water

Physical indicators

Exterior Yellow or brown liquid

pH value 6.0-9.0

Viscosity, 25°C <1000mPa.s

- Instructions**
- It can be added directly and is not recommended for dilution.
 - The amount of paper coating added per ton of product is 500~5000g. The consumption of papermaking white water per ton of paper is 100~500g. The addition amount in the water treatment industry is 100~1000ppm. The optimal addition amount is determined according to the actual situation on site.
 - Added during paper coating configuration. The adding point for papermaking white water is the white water pool under the net or the white water tank outside the machine. The water treatment addition point is generally a location with rich foam and easy dispersion of defoaming agent.
-

Precautions	<ul style="list-style-type: none">● There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water● Storage at room temperature (5-40°C), away from direct sunlight● Refer to the product's Material Safety Data Sheet (MSDS) before use
Usage	<ul style="list-style-type: none">● Not for human injection
restrictions	<ul style="list-style-type: none">● This product is not tested or represented as suitable for medical or pharmaceutical use
Package	<ul style="list-style-type: none">● 25kg/200kg plastic drum or 1000kg IBC drum

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.