

Technical Data Sheet

AF-919

Ingredient Mineral oil and hydrophobic particles

Warranty 6 months (kept in a cool, dry place at room temperature)

Applications AF-919 is used in

- Water-based adhesive
- Pressure sensitive adhesive
- Water-based paint, ink
- All kinds of latex paint

Features

- Permanent foam suppression
- Good compatibility

Physical indicators

Exterior Grayish white or yellowish liquid

Active content 100%

Viscosity, 25°C 100-1500mPa.s

Instructions

- It can be used directly, or can be pre-dispersed after use.
- The addition amount is generally 0.1~0.6%, and the optimal addition amount is adjusted according to the actual situation on site.

Precautions	<ul style="list-style-type: none">● There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water● Storage at room temperature (5-40°C), away from direct sunlight● Refer to the product's Material Safety Data Sheet (MSDS) before use
Usage	<ul style="list-style-type: none">● Not for human injection
restrictions	<ul style="list-style-type: none">● This product is not tested or represented as suitable for medical or pharmaceutical use
Package	<ul style="list-style-type: none">● 25kg/50kg/180kg plastic drum or 850kg IBC drum

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.